Application No.: 10/671,309 Docket No.: EL0506 US NA

Page 2

## **AMENDMENT TO CLAIMS**

- 1. (Cancelled),
- 2. (Currently Amended) An electrically conductive paste comprising at least one conductive powder selected from copper powder, nickel powder, copper-nickel alloy powder, and mixtures thereof; a glass frit which is free of lead, cadmium and bismuth, and which has a softening point of 530 to 650°C, a coefficient of thermal expansion of 9.0 to 11.5 ppm/°C wherein the powder and glass frit are dispersed in an organic medium The conductive paste of claim 1, wherein the glass frit is a borosilicate alkaline earth glass containing, based on the weight of the oxides therein, 30 to 60% of BaO + SrO, 20 to 45% of B<sub>2</sub>O<sub>3</sub> + ZnO + Na<sub>2</sub>O, and 0 to 7% of Na<sub>2</sub>O.
- 3. (Currently Amended) The conductive paste of <u>Claim any one of Claim claims</u> 1 or 2 containing 55.0-85 wt % inorganic solids, comprising powder and frit, wherein 5-20 wt % is glass frit.
- 4. (Currently Amended) The conductive paste of any one of Claims 2 or 3 1 3 wherein said organic medium comprises methyl methacrylate and butylcarbitolacetate.
- 5. (Currently Amended) The use of the conductive paste of any one of Claims 2 or 3 1 4 as a terminal electrode composition for multilayer capacitors.
  - 6 (Currently Amended) A method of forming a terminal electrode comprising:
    - (a) forming the conductive paste of Claim 2 any one of Claims 1-4;
    - (b) coating the composition of (a) onto a terminal electrode-forming site of a multilayer capacitor; and
    - (c) firing the multilayer capacitor in (b) to form a finished terminal electrode.
- 7. (Currently Amended) A multilayer capacitor utilizing the conductive paste of Claim 2 any one of Claims 1-4.